Page 1 of 3

02292013 A



(11) Publication number:

02292013 A

## Generated Document

PATENT ABSTRACTS OF JAPAN

(21) Application number: 01111772

(51) Intl. Cl.: B29C 45/26 B29C 33/38 B29C 45/72

(22) Application date: 29.04.89

(30) Priority:

(43) Date of application publication:

03.12.90

(84) Designated contracting States:

(74) Representative:

(72) Inventor: MASUHARA HIDEKAZU

KOMIYA SHIGEO

(71) Applicant: SOGO SHIKA IRYO

KENKYUSHO:KK

(54) INJECTION MOLDING METHOD OF

**PHOTOPOLYMERIZATION** RESIN AND INJECTION MOLDING APPARATUS

THEREOF

(57) Abstract:

cavities formed in a male and female mechanical strength by press-casting excellent dimensional accuracy or efficiently a resin molding having photopolymerization resin into mold made up of a transparent PURPOSE: To manufacture

https://www.delphion.com/cgi-bin/viewpat.cmd/JP02292013A2

Page 2 of 3

material, and introducing and irradiating photopolymerization fradiating light into the cavity from the outside.


02292013 A

nozzle 3 by means of a screw 2. Next, photopolymerization resin, a molding CONSTITUTION: Photosetting resin 6 is inputted into a photosetting resin screw and a cooling pipe in the mold molding apparatus can be simple and injection-molded at low temperature kneading supplier 7, and then pressare not required, the structure of the accuracy. And, since a heater in the side molding mold 4b is withdrawn photosetting resin molding is taken photopolymerization resin 6 within molding mold 4b, and the movable for opening the molding mold, and movable side transparent molding casted into a cavity 5 formed in a visible light produced by halogen glass 4c and movable transparent mold 4b through a cylinder 1 and the cavity 5 through a reinforced fixed side molding mole 4a and and has excellent dimensional can be obtained, which can be thus a polymerized and cured out thereof. By employing amps is irradiated to the small in size.

COPYRIGHT: (C)1990, IPO&Japio

Page 3 of 3

https://www.delphion.com/cgi-bin/viewpat.cmd/JP02292013A2



## This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
□ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
COLOR OR BLACK AND WHITE PHOTOGRAPHS
GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.